

**Typical chemical and physical properties**

ADDAPT® Foamstop™ 666V is a **water soluble** foam control agent.

**It is a proprietary blend of polyalkylene glycols and surface-active components**

All constituents are EINECS registered and comply with the FDA regulation (incidental contact with foodstuff). FDA-no: 21 CFR § 173.340

Appearance	Light, turbid liquid
Viscosity at 25 °C	<500 mPa·s
Density at 25 °C	1.02 – 1.05 g/cm <sup>3</sup>
Flash point	>120 °C
Boiling point polyalkylene glycols	>250 °C
Mineral oil content	0%

*This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.*

**Applications and typical treat level recommended**

Paint industry	0.05 to 0.5 % wt. on total formulation
Printing ink industry	0.05 to 0.5 % wt. on total formulation
Floor polish- and cleaner industry ( <b>high temperature range</b> )	
Aqueous hydraulic fluids	
Aqueous metalworking fluids	

**Benefits**

- 100% solubility in water; no turbidity or haze of the liquid phase in clear systems.
- Maintains the defoaming properties over a prolonged period of time.
- Filters and spray nozzles will not be blocked whilst using ADDAPT® Foamstop™ 666V.
- Effective over a wide pH range (2 to 12).
- High temperature range 40 – 75 °C.
- Biodegradable.
- Does not contain mineral oil, amines, nitrates or fluorides.
- Metal surfaces are readily cleaned by rinsing with tap water.
- No paint or plating adhesion problems expected when the defoamer is applied.

# ADDAPT<sup>®</sup> Foamstop<sup>™</sup> 666V

---

<b>Safety and Handling</b>	Please read Material Safety Data Sheet (MSDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.

---

**Quality Policy**                      The objective of our quality policy is the continuous fulfilment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT<sup>®</sup> Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001: 2015.

---

**Liabilities**                              *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
NL-5704 RJ Helmond  
The Netherlands  
Tel: + 31 - 492 59 75 75  
Fax: + 31 - 492 55 29 55  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

Publication Number FO82429  
© ADDAPT Chemicals BV 2022  
Version 2: 2022

