

### Typical chemical and physical properties

ADDAPT<sup>®</sup> Foamstop<sup>™</sup> CCB is a cost-effective foam control agent for emulsion systems based on PVAC, VA/VEOVA, styrene/acrylics or pure acrylics.

**It is a proprietary blend of PAG's and surface active compounds based on renewable resources.**

All constituents comply with the FDA regulation (incidental contact with foodstuff).

Appearance	Yellowish, turbid liquid
Active content	100%
Density at 25 °C	0.89 – 0.91 g/cm <sup>3</sup>
Viscosity at 25 °C (Brookfield #2 – 50 rpm)	<250 mPa·s
Flash point	>100 °C
Solubility	
Water	Emulsifiable
Mineral oil	Miscible

*This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.*

### Applications and typical treat level recommended

Paint industry	0.15 to 0.30 % wt. based on total formulation
Adhesive industry	0.10 to 0.30 % wt. based on total formulation
Printing inks	
Floor polish industry	
Wastewater treatment	

### Benefits

ADDAPT<sup>®</sup> Foamstop<sup>™</sup> CCB is recommended for the use in pigmented Emulsion paints, Printing Inks as well as Emulsion based Adhesives.

ADDAPT<sup>®</sup> Foamstop<sup>™</sup> CCB is easily emulsifiable. 2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage.

Very suitable for cost effective, high PVC emulsion paints.

Maintains the defoaming properties over a prolonged period of time.

**Does not contain hydrocarbons, nonylphenol derivatives, silicones/siloxanes, amines, nitrates and fluorides.**

No intercoat adhesion problems are expected when the defoamer is applied.

# ADDAPT<sup>®</sup> Foamstop<sup>™</sup> CCB

---

<b>Safety and Handling</b>	Please read Material Safety Data Sheet (MSDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.

---

**Quality Policy**                      The objective of our quality policy is the continuous fulfilment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT<sup>®</sup> Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001:2015.

---

**Liabilities**                              *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
NL-5704 RJ Helmond  
The Netherlands  
Tel: + 31 - 492 - 59 75 75  
Fax: + 31 - 492 - 55 29 55  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

Publication Number FO82502  
© ADDAPT Chemicals BV 2022  
Version 4: 2022

