

ADDAPT[®] Foamstop™ WS 17 Foam Control Agent Water Soluble

Typical chemical and physical properties

ADDAPT® Foamstop™ WS 17 is a highly effective, **completely water-soluble** foam control agent.

It is a proprietary blend of polyalkylene glycols and surface-active components

Appearance Yellowish, slightly turbid liquid

Viscosity at 25 °C <75 mPa·s

pH 6.5 - 7.5

Density at 25 °C 1.07 – 1.13 g/cm³

Flash point >100 °C

Mineral oil content 0%

FDA-no 21 CFR § 173.340

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

Paint industry

0.05 to 0.5 % wt. on total formulation

Printing Ink industry(Flexo Inks)

0.05 to 0.5 % wt. on total formulation

Floor polish industry

Aqueous hydraulic fluids

Aqueous metalworking fluids

Cleaners/Detergents/Rinse Aids 0.1 to 0.75% wt. on total formulation

Acidic and Alkaline media

Benefits

100% solubility in water; no turbidity or haze of the liquid phase in clear systems.

 $\mathsf{ADDAPT}^{\$}$ Foamstop $\mathsf{^{TM}}$ WS 17 is designed for aqueous systems with extreme pH values.

Effective over a wide pH range (1 to 13).

It maintains the defoaming properties over a prolonged period of time.

Filters and spray nozzles will not be blocked whilst using ADDAPT[®] Foamstop™ WS 17

Biodegradable.

Metal surfaces are readily cleaned by rinsing with tap water.

No paint or plating adhesion problems expected when the defoamer is applied.







ADDAPT® Foamstop™ WS 17

Safety and Handling Please read Material Safety Data Sheet (MSDS) before handling.

Product Specification This information is available on request through our local representative.

Packaging This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfilment of the internal

and external requirements agreed upon with our partners with regards to

everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of

the NEN-EN-ISO-Standard 9001: 2015

Liabilities

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 NL-5704 RJ Helmond The Netherlands

Tel: +31 - 492 - 59 - 75 - 75 Fax: +31 - 492 - 55 - 29 - 55 E-mail: info@addapt-chem.com

Home page: http://www.addapt-chem.com

Publication Number FO82600 © ADDAPT Chemicals BV 2012

Version 5: 2022