

Typical chemical and physical properties Water-soluble foam control agent. Gives no turbidity or haze of the liquid phase in clear systems and maintains the defoaming properties over a prolonged period of time. Also suitable for a wide range of solvent-borne systems.

Proprietary blend of polyalkylene glycols and surface-active components.

Appearance	Liquid
Solubility	
Water	Emulsifiable
Density at 25°C	1,04 - 1,09 g/ml
Viscosity at 25°C	100 - 400 mPa·s
Water solubility	Soluble

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets	Coating industry Ink industry Cleaning industry Metalworking industry
Applications	Paints and lacquer Pigment concentrates Printing inks Floor polish- and cleaner Aqueous metalworking fluids Solvent-based systems - Clear wood lacquers - Alkyd Paints - Two-pack epoxies - PU-systems
Recommended dosage/usage	0,05 to 1,0 % wt. on total formulation Suitable as Food contact material

- No haze of the liquid phase in clear systems.
- Good compatibility with a wide range of water- and solvent-borne systems.
- Maintains the defoaming properties over a prolonged period of time.
- No paint or plating adhesion problems expected when the defoamer is applied.
- Does not block filters and spray nozzles.
- Effective over a wide pH range (0 to 14).

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)
Quality Policy	The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance. ☐ The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.
Liabilities	<i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i>

ADDAPT Chemicals BV
Speltdijk 1
5704 RJ Helmond
The Netherlands
Tel: + 31 (0)492 597575
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

