

Technical Data Sheet

Foamstop™ OPE 032

Defoamer – Coatings & Industrial

Article number: Verification date: Version:

FO82310 18/02/2025 2.1

Typical chemical and Polymeric defoamer especially formulated for the production of paper, pulp as well as for the production of Eternit. physical properties

Blend of fatty alcohols and esters.		
Appearance	Liquid	
Active content	~100%	
Density at 25°C	0,89 - 0,93	g/ml
Viscosity at 25°C	10 - 100	mPa⋅s
dad as a guidaling only. For specificatio	ne nlazea conei	ult the Certificate of Analys

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and		
treat level	Markets	Paper industry Eternit industry
	Applications	Paper Eternit production
	Recommended dosage/usage	Apply the product in its natural state by aspersion or by dosing pump and adjust the initial dosage according to the requirements. May also be distributed with a water dilution system and or with a special metering system for automatic dosing to the process, which means product will automatically added only when needed. Paper 100 – 250 ppm Eternit 100 – 250 ppm

Key benefits

- Inherently biodegradable -

· Shows excellent performance in the control of foams and improves the flow and reduces the viscosity of the medium.

· Leaves no residues in the pipes or valves of the equipment used.









Technical Data Sheet

Foamstop[™] OPE 032 Defoamer – Coatings & Industrial

Article number: Verification date: Version: FO82310 18/02/2025 2.1

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.		
Product Specification	This information is available on request through our local representative.		
Packaging	This information is available on request through our local representative.		
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)		
Quality Policy	The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.		
	The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.		
Liabilities	All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.		

ADDAPT Chemicals BV Speltdijk 1 5704 RJ Helmond The Netherlands Tel: + 31 (0)492 597575 E-mail: <u>info@addapt-chem.com</u> Home page: <u>http://www.addapt-chem.com</u>





