

Foamstop™ OPE 032 Defoamers – Coatings & Industrial

Article number: FO82310
Verification date: 01/08/2024
Version: 2

Product description

Polymeric defoamer especially formulated for the production of paper, pulp as well as for the production of Eternit.

Typical chemical and physical properties

Chemical nature Blend of fatty alcohols and esters.

Appearance Liquid

Active content ~100%

Odour Characteristic

Density at 25°C 0,89 - 0,93 g/ml

Viscosity at 25°C 10 - 100 mPa·s

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets Paper industry

Eternit industry

Applications Paper

Eternit production

Recommended dosage/usage Apply the product in its natural state by aspersion or by dosing pump and

adjust the initial dosage according to the requirements.

May also be distributed with a water dilution system and or with a special metering system for automatic dosing to the process, which means product

will automatically added only when needed.

Paper 100 – 250 ppm Eternit 100 – 250 ppm

Key benefits

- Inherently biodegradable -
- Shows excellent performance in the control of foams and improves the flow and reduces the viscosity of the medium.
- Leaves no residues in the pipes or valves of the equipment used.











Technical Data Sheet

Foamstop™ OPE 032 Defoamers – Coatings & Industrial

Article number: FO82310 Verification date: 01/08/2024 Version: 2

Safety and Handling Please read Safety Data Sheet (SDS) before handling.

Product Specification This information is available on request through our local representative.

Packaging This information is available on request through our local representative.

Storage The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety

details read the Safety Data Sheet (SDS)

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our

partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

Liabilities

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 5704 RJ Helmond The Netherlands Tel: +31 (0)492 597575 E-mail: info@addapt-chem.com

Home page: http://www.addapt-chem.com







