

Product description

Concentrated and versatile silicone foam control agent. It can be used in both aqueous and non-aqueous systems. Maintains its defoaming properties.

Typical chemical and physical properties

Chemical nature	100% active silicone compound containing minerals.	
Appearance	Pass	
Active content	~100%	
Solubility		
Water	Emulsifiable	
Odour	Characteristic	
Density at 25°C	0,95 - 1,10	g/ml
Viscosity at 25°C	2000 - 4000	mPa.s

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets	Coating industry Ink industry Metalworking industry
Applications	Paints Printing inks Cutting oils Epoxy resin systems
Recommended dosage/usage	10 - 100 ppm 2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage

Key benefits

- Free of MOSH/MOAH -

- Maintains the defoaming properties over a prolonged period of time.
- Disperses easily, requiring only mild agitation.
- Can be applied neat or dispersed in organic solvents like: ethyl acetate; MIBK; toluene; amyl acetate; kerosine; xylene; 2-ethyl hexanol; white spirits; perchloro ethylene.
- Prevents the formation of macro-foam and reduces the formation of micro-foam. When used in pigmented systems; it does not influence the recoatability.

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)

Quality Policy	<p>The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.</p> <p>The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.</p>
-----------------------	--

Liabilities	<p><i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i></p>
--------------------	---

ADDAPT Chemicals BV
Speltdijk 1
5704 RJ Helmond
The Netherlands
Tel: + 31 (0)492 597575
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

