

**Typical chemical and physical properties** Effective and sustainable foam control agent recommended for use in pigmented low-VOC emulsion paints, (flexo-) printing inks as well as clear lacquers and also for emulsion-based adhesives.

**Proprietary blend of components largely based on renewable resources.**

|                   |                  |
|-------------------|------------------|
| Appearance        | Liquid           |
| Active content    | ~100%            |
| Solubility        |                  |
| Water             | Dispersible      |
| Mineral oil       | Dispersible      |
| Density at 25°C   | 0,92 - 0,98 g/ml |
| Viscosity at 25°C | 400 - 1500 mPa·s |

*This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.*

### Application and treat level

|                          |                                                                                                                                                            |
|--------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Markets                  | Ink industry<br>Coating industry<br>Adhesive industry<br>Lubricants industry<br>Water treatment industry                                                   |
| Applications             | (Flexo-) Printing inks<br>Paints<br>Adhesive<br>Floor polish<br>Lubricant<br>Wastewater treatment                                                          |
| Recommended dosage/usage | 0,1 to 1,0% wt. based on total formulation formulation<br><br>2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage |

### Suitable as Food contact material

- Very suitable for cost-effective, high PVC emulsion paints, textured masonry coatings and renders/plasters (putz).
- Maintains the defoaming properties over a prolonged period of time.
- Disperses easily, requiring only mild agitation.
- Recommended for the use in pigmented VOC free emulsion paints, (flexo-) printing inks as well as clear lacquers and also for emulsion based adhesives.
- Easy emulsifiable.
- No intercoat adhesion problems are expected when the defoamer is applied.

|                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Safety and Handling</b>   | Please read Safety Data Sheet (SDS) before handling.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Product Specification</b> | This information is available on request through our local representative.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Packaging</b>             | This information is available on request through our local representative.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>Storage</b>               | The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Quality Policy</b>        | <p>The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.</p> <p><input type="checkbox"/> The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Liabilities</b>           | <p><i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i></p> |

ADDAPT Chemicals BV  
Speltdijk 1  
5704 RJ Helmond  
The Netherlands  
Tel: + 31 (0)492 597575  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

