

**Product description**

Highly effective and completely water-soluble foam control agent. 100% soluble in water, with no turbidity or haze of the liquid phase in clear systems.

**Typical chemical and physical properties**

|                   |  |       |
|-------------------|--|-------|
| Chemical nature   | Proprietary blend of polyalkylene glycols and surface-active components. |       |
| Appearance        | Liquid   |       |
| Solubility        | Soluble  |       |
| Water             |  |       |
| Odour             | Characteristic   |       |
| Density at 25°C   | 1,07 - 1,13  | g/ml  |
| Viscosity at 25°C | 20 - 75  | mPa·s |
| Water solubility  | Soluble  |       |

*This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.*

**Application and treat level**

|                          |   |
|--------------------------|---|
| Markets                  | Metalworking industry<br>Coating industry<br>Ink industry<br>Cleaner industry<br>Engineering industry   |
| Applications             | Aqueous metalworking fluids<br>Paints<br>Printing inks (Flexo)<br>Floor polish and cleaner<br>Aqueous hydraulic fluids<br>Acidic and alkaline media |
| Recommended dosage/usage | Cleaners 0,1 to 0,75% wt. on total formulation<br>Other 0,05 to 0,5% wt. on total formulation   |

**Suitable as incidental food contact**

**Key benefits**

- Inherently biodegradable -- APEO/NPEO free -- Free of MOSH/MOAH -
- Completely soluble in water; no turbidity or haze of the liquid phase in clear systems.
- Designed for aqueous systems with extreme pH values (1 - 13).
- Maintains the defoaming properties over a prolonged period of time.
- Does not block filters and spray nozzles.
- Metal surfaces are readily cleaned by rinsing with tap water.
- No paint or plating adhesion problems expected when the defoamer is applied.

---

|                              |  |
|------------------------------|--|
| <b>Safety and Handling</b>   | Please read Safety Data Sheet (SDS) before handling.   |
| <b>Product Specification</b> | This information is available on request through our local representative.   |
| <b>Packaging</b>             | This information is available on request through our local representative.   |
| <b>Storage</b>               | The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS) |

---

|                       |  |
|-----------------------|--|
| <b>Quality Policy</b> | <p>The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.</p> <p>The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.</p> |
|-----------------------|--|

---

|                    |   |
|--------------------|---|
| <b>Liabilities</b> | <p><i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i></p> |
|--------------------|---|

ADDAPT Chemicals BV  
Speltdijk 1  
5704 RJ Helmond  
The Netherlands  
Tel: + 31 (0)492 597575  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

