

Typical chemical and physical properties

ADDAPT® Clean MoB is an active water soluble cleaning agent for **Non-Aluminium** as well as **Aluminium surfaces** having a **pH of 11 - 12**. It was especially designed as **Mould-Cleaning Agent** for removing resinous residues.

It is a proprietary blend of coupling agents and organic compounds.

All constituents are EINECS registered and comply with the FDA regulation (§ 170.300 - incidental contact with foodstuff)

Solubility	
Water	> 30 %
Mineral oil	< 0.01 %
pH	11.0 - 13.0 (10 % solution)
Biodegradability	
Total formulation	> 75% [OECD 302B]
Non-ionic detergent	> 90% [OECD 302B]

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

- Removes fat, greases, nicotine films, tar film, rust film
- Cleans soiled surfaces of stainless steel, concrete, plastics, ceramics, glass and wood
- Mould Cleaning Agent

Dilute with warm water or use on warm surfaces. Dilution ratio: **1:3 or 1 : 25 with water.** High pressure equipment; dilution ratio **1 : 70 with water.** Spray soiled surface and wait for a few minutes before rinsing with water. Successfully removes resinous residues from both Stainless Steel and Aluminium Moulds without affecting metal surface despite the high pH.

Benefits

The product was especially designed to remove residual resin like PU- or Epoxy resin from Stainless Steel as well as Aluminium moulds.

The Aluminium surface is not affected despite the high pH.

Suitable for the food and beverage industry and uses in kitchens.

Ingredients are generally recognised as safe (**GRAS**)

Easy to handle liquid

Free of Nonyl Phenol-derivatives

Phosphate free

Non toxic

ADDAPT® Clean MoB

Safety and Handling	Please read Material Safety Data Sheet (MSDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001 : 2015.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV
Speltdijk 1
NL-5704 RJ Helmond
The Netherlands
Tel: + 31 - 492 - 59 - 75 - 75
Fax: + 31 - 492 - 55 - 29 - 55
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

Publication Number CL81216
© ADDAPT Chemicals BV 2003
Version 4: 2019

