
Typical chemical and physical properties

Tac E 60 is a biodegradable tack improver based on natural rubber dissolved in a vegetable oil for lubricating oils and metal working processes in general.

| | |
|--------------------|----------------------------------|
| Appearance | Highly viscous dark amber liquid |
| Viscosity at 40 °C | 21000 - 30000 mPa.s |
| Density at 15 °C | 0.90 – 0.94 g/cm ³ |
| Flash point | > 300 °C, COC |

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

Metalworking processes, oil based rust preventives, and machine oil, hydraulic fluids, General purpose gear, Spindle automotive chassis grease, Wire rope dressing

5 % in the final, ready to use solution

Benefits

Consistent high tackiness potency and good shear stability due to good manufacturing practices and long term experience in quality.

Tac E 60 is biodegradable and contains no mineral or synthetic oil.

Free of particulate or non-dissolved polymer will not clog filters.

Premium quality for demanding service

Caution

Addition of Tac E 60 should be made at the lowest mixing temperature possible. The mixing temperature must not exceed 50 °C, otherwise premature oxidative degradation may occur.

Product should not be stored at temperatures below 15 °C and be protected from frost.

ADDAPT[®] Tac E 60

| | |
|------------------------------|--|
| Safety and Handling | Please read Material Safety Data Sheet (MSDS) before handling. |
| Product Specification | This information is available on request through our local representative. |
| Packaging | This information is available on request through our local representative. |

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT[®] Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001:2015.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV
Speltdijk 1
NL-5704 RJ Helmond
The Netherlands
Tel: + 31 - 492 - 59 - 75 - 75
Fax: + 31 - 492 - 55 - 29 - 55
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

Publication Number T87701
© ADDAPT Chemicals BV 2003
Version 4: 2019

