

**Typical chemical and physical properties** Active water-soluble cleaning agent for aluminium as well as non-aluminium surfaces having a pH of 11 - 12.

**Proprietary blend of coupling agents and organic compounds.**

Appearance	Liquid
Solubility	
Water	> 30%
Mineral oil	Insoluble
Odour	Mild
pH 10% in water at 25°C	11,0 - 13,0

*This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.*

**Application and treat level**

Markets	Food and beverage industry
Applications	Mould Cleaner agent Aluminium Stainless steel Concrete Plastics Ceramics Glass Wood
Recommended dosage/usage	- Removes fat, greases, nicotine films, tar film, rust film - Dilution ratio: Dilute with warm water or use on warm surfaces. Dilution ratio: 1:3 or 1 : 25 with water - Cleans soiled surfaces of stainless steel, concrete, plastics, ceramics, glass and wood - High pressure equipment; dilution ratio: 1 : 70 with water. Spray soiled surface and wait for a few minutes before rinsing with water. - Mould Cleaning Agent - Successfully removes resinous residues from both stainless steel and aluminium moulds without affecting metal surface despite the high pH.

**Suitable as Incidental food contact**

**Key benefits**

- Readily biodegradable -- APEO/NPEO free -- Free of phosphates -
- The product was especially designed to remove residual resin like PU- or Epoxy resin from Stainless Steel as well as Aluminium moulds.
- The Aluminium surface is not affected despite the high pH.
- Efficiently removes fat, greases, nicotine, tar and rust films.
- Very suitable for the food and beverage industry and uses in kitchens.
- Non-toxic.

<b>Safety and Handling</b>	Please read Safety Data Sheet (SDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.
<b>Storage</b>	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)
<b>Quality Policy</b>	<p>The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.</p> <p>The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.</p>
<b>Liabilities</b>	<p><i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i></p>

ADDAPT Chemicals BV  
Speltdijk 1  
5704 RJ Helmond  
The Netherlands  
Tel: + 31 (0)492 597575  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

