

Technical Data Sheet

Coolant™ SiF-12SC Antifreeze

Article number: CO81234 Verification date: 01/08/2024 Version: 2

Product description

Corrosion inhibitor package for high-performance engine coolant, free of borates, phosphates, amines, nitrites and nitrates. Meets the requirements of G12++ and G13 engine coolants.

Typical chemical and physical properties

Chemical nature Concentrated aqueous solution of organic acids salts (Si-OAT technology).

Freezing point -18°C

Solubility

Water Miscible

Odour Characteristic

Density at 20°C 1,20 - g/ml

Solubility in water and MEG Complete

Colour <500 Pt-Co

Water content 5% in MEG <3,00 wt%

pH 8% in MEG & 50% in water at 20°C 7,5 - 10,0

Reserve alkaline 0.1 HCl/10 ml - 8%/MEG >8 min

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets Automotive industry

Industrial machinary

Applications Engine coolants

Antifreeze

Recommended dosage/usage The requirement of ASTM D 3306 or ASTM D 4985 are fully met by adding

8% w/w of Coolant SiF-12SC to MEG or MPG.

Add Coolant SiF-12SC to the MEG and homogenize for 30 minutes.

Key benefits

- Free of phospates -- Free of amines -- Free of borates -- Free of nitrates -- Free of nitrites -

International, National and Military Standards met by Engine Coolant based on Coolant SiF-12SC:
BS 6580 (UK) – FVV Heft R 443 (D) – Afnor R 15/601 (1) (F) – SAE J 1034 (1) – JIS K 2234 (J) – KSM 2142 (K) – CUNA NC 956-16 (I) – UNE 26361-88 (E) – EMPA (CH) – ASTM D 3306 and 4985 – NATO S 759 – E/L 1415c (MIL Italy)

OEM Specifications met by Engine Coolant based on Coolant SiF-12SC:

(1) Except reserve alkalinity VW TL 774 G (G12++)











Technical Data Sheet

Coolant™ SiF-12SC Antifreeze

CO81234 Article number: Verification date: 01/08/2024 Version:

Please read Safety Data Sheet (SDS) before handling. Safety and Handling

Product Specification This information is available on request through our local representative.

Packaging This information is available on request through our local representative.

The product should be stored at a temperature of no less than 10 $^{\circ}$ C and no more than 25 $^{\circ}$ C and away from light. For more safety Storage

details read the Safety Data Sheet (SDS)

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our

partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

Liabilities

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 5704 RJ Helmond The Netherlands Tel: + 31 (0)492 597575 E-mail: info@addapt-chem.com

Home page: http://www.addapt-chem.com







