

Product description

Corrosion inhibitor package for high-performance engine coolant, free of silicates, amines, phosphates, nitrites and nitrates. Meets the requirements of G12, G12+ and G13 engine coolants.

Typical chemical and physical properties

Chemical nature	Concentrated aqueous solution of organic acids salts (OAT technology).	
Freezing point	-10°C	
Solubility		
Water	Miscible	
Odour	Characteristic	
Density at 20°C	1,10 - 1,15	g/ml
Colour	<500	Pt-Co
Foaming tendency test	Low	
Water content 5% in MEG	<5,0	wt%
pH 8% in MEG & 50% in water at 20°C	7,5 - 9,5	
Reserve alkaline 0.1 HCl/10 ml - 8%/MEG	>4	

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets	Automotive industry Industrial machinery
Applications	Engine coolants Antifreeze
Recommended dosage/usage	The requirement of ASTM D 3306 or ASTM D 4985 are fully met by adding 8% w/w of Coolant SiF-8SC to MEG or MPG. Add Coolant SiF-8SC to the MEG and homogenize for 30 minutes.

Key benefits

International, National and Military Standards met by Engine Coolant based on Coolant SiF-8SC:
BS 6580 (UK) – FVV Heft R 443 (D) – Afnor R 15/601 (1) (F) – SAE J 1034 (1) – JIS K 2234 (1) (J) – KSM 2142 (K) – CUNA NC 956-16 (I) – UNE 26361-88 (E) – EMPA (CH) – ASTM D 3306 and 4985 – NATO S 759 – E/L 1415c (MIL Italy)

OEM Specifications met by Engine Coolant based on Coolant SiF-8SC:
Porsche/VW/Audi/Seat/Skoda TL 774 D/D (2) – Mercedes MB 325.3 – Ford ESE M97B49-A – CUMMINS 85T8-2 (1) – Man N. Man 248 and 324 – Wartsilia 32-9011 (C.W.) – Pegaso GM US 6277 M – Renault 41-01-001 – Ford WSS-M97B44-D – Chrysler MS 9176 – CUMMINS 90T8-4 – Mack 014GS17004 – MAN B&W D 36 5600 – GM 1899 M (1) – Navistar B-1, Type III – VOLVO (Reg. N° 260) – FORD ESD M97 B49-A – OPEL GM QL 130100 – Leyland Trucks LTS 22 AF 10 – John Deere H 24 B1 and C1 – Deutz/MWN 0199-2091 2 Auflage (C.W.)

- (1) Except reserve alkalinity – (C.W.) = coolant water
- (2) Except water content

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)

Quality Policy	<p>The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.</p> <p>The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.</p>
-----------------------	--

Liabilities	<p><i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i></p>
--------------------	---

ADDAPT Chemicals BV
Speltdijk 1
5704 RJ Helmond
The Netherlands
Tel: + 31 (0)492 597575
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

