

Typical chemical and physical properties Biodegradable tack improver based on natural rubber dissolved in vegetable oil for lubricating oils and metalworking processes in general. Appearance: highly viscous dark amber liquid.

Natural rubber in vegetable oil.

Appearance	Medium Yellow
Active content	~100%
Odour	Oil

Application and treat level

Markets	Metalworking industry Lubricants industry
Applications	Metalworking processes Chain saw oils Machine oils Hydraulic fluids Spindle automotive chassis grease Wire rope dressing General purpose gear
Recommended dosage/usage	5 % in the final, ready to use solution. Caution: Addition should be made at the lowest mixing temperature possible. The mixing temperature must not exceed 50 °C, otherwise premature oxidative degradation may occur.

Key benefits

- PFAS Free -- Free of MOSH/MOAH -- Free of silicone oils -
- Consistent high tackiness potency and good shear stability due to good manufacturing practices and long term experience in quality.
- Free of mineral and synthetic oil.
- Free of particulate or non-dissolved polymer will not clog filters.
- Premium quality for demanding service.
- Improved lubricant adhesion and efficiency.
- Reduces splashing.

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)
Quality Policy	The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance. ☐ The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.
Liabilities	<i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i>

ADDAPT Chemicals BV
Speltdijk 1
5704 RJ Helmond
The Netherlands
Tel: + 31 (0)492 597575
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

