

### **Technical Data Sheet**

# TAC™ E60 Tackifiers

Article number: T87701 Verification date: 01/08/2024 Version: 2

#### **Product description**

Biodegradable tack improver based on natural rubber dissolved in vegetable oil for lubricating oils and metalworking processes in general. Appearance: highly viscous dark amber liquid.

Typical chemical and physical properties

Chemical nature Natural rubber in vegetable oil.

Active content ~100%

Odour Oil

Application and treat level

Markets Metalworking industry

Lubricants industry

Applications Metalworking processes

Chain saw oils Machine oils Hydraulic fluids

Spindle automotive chassis grease

Wire rope dressing General purpose gear

Recommended dosage/usage  $\,$  5 % in the final, ready to use solution.

Caution: Addition should be made at the lowest mixing temperature possible. The mixing temperature must not exceed 50  $^{\circ}$ C, otherwise

premature oxidative degradation may occur

#### Key benefits

- Consistent high tackiness potency and good shear stability due to good manufacturing practices and long term experience in quality
- quality.
  Free of mineral and synthetic oil.
- Free of particulate or non-dissolved polymer will not clog filters.
- Premium quality for demanding service.
- Improved lubricant adhesion and efficiency.
- Reduces splashing.









## **Technical Data Sheet**

# TAC™ E60 **Tackifiers**

T87701 Article number: Verification date: 01/08/2024 Version:

Safety and Handling Please read Safety Data Sheet (SDS) before handling.

**Product Specification** This information is available on request through our local representative.

**Packaging** This information is available on request through our local representative.

The product should be stored at a temperature of no less than 10  $^{\circ}$ C and no more than 25  $^{\circ}$ C and away from light. For more safety Storage

details read the Safety Data Sheet (SDS)

**Quality Policy** The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our

partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

Liabilities

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 5704 RJ Helmond The Netherlands Tel: +31 (0)492 597575 E-mail: info@addapt-chem.com

Home page: http://www.addapt-chem.com







