

ADDAPT® BioWet 25L Biodegradable Wetting Agent

Typical chemical and physical properties

ADDAPT® BioWet 25L is a **solvent free**, ready biodegradable wetting agent for aqueous lacquers and paints.

It is a Polyhydroxy - Amide in water.

Appearance Transparent liquid

Odour Characteristic

Density 1.13 - 1.18 g/cm³ at 25 ℃

Viscosity < 50 mPa.s at 25 $^{\circ}$ C pH 5.0 - 8.0 at 25 $^{\circ}$ C

Solubility

Water 100%

Biodegradation Readily Biodegradable (OECD 301F)

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

- Coatings and Lacquers
- 0.5 -2.0 % wt. based on total formulation

- Printing Inks (OPV)
- Stain and Primer

Benefits

The multifunctional nature of ADDAPT® BioWet 25L allows to provide the necessary wetting properties for water based systems such as paints, adhesives, printing inks.

ADDAPT® BioWet 25L exhibits a high surface energy that leads to an excellent wetting of the (paper) coating without an increase of the water absorption (low COBB value).

ADDAPT® BioWet 25L is non-foaming.

ADDAPT® BioWet 25Lis recommended to improve:

- ✓ Wet-Edge (open time) of emulsion paints and lacquers
- ✓ Gloss improvement of emulsion lacquers
- ✓ Penetration
- ✓ Pigment grinding efficiency
- ✓ Wetting of pigment surface
- ✓ Improves the "FLOP" of Aluminium pigments

pH application range: 4 - 13







ADDAPT® BioWet 25L

Publication Number B87736

Version 3: 2019

© ADDAPT Chemicals BV 2015

Safety and Handling Please read Material Safety Data Sheet (MSDS) before handling.

Product Specification This information is available on request through our local representative.

Packaging This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal

and external requirements agreed upon with our partners with regards to

everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles

of the NEN-EN-ISO-Standard 9001: 2015.

Liabilities

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 NL-5704 RJ Helmond The Netherlands

Tel: + 31 - 492 - 59 75 75

Home page: http://www.addapt-chem.com

Fax: + 31 - 492 - 55 29 55 E-mail: info@addapt-chem.com

