
Typical chemical and physical properties

ADDAPT® HS 51 is a non-toxic and non-flammable water repellent for wood substrates only.

It is a proprietary blend of additives

Appearance

Milky liquid

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

Applications and typical treat level recommended

- As a milky aqueous treatment for wood substrates

It is available as a ready to use product or as a concentrate which requires dilution before usage (ADDAPT® HS 51C)

Benefits

Easy to handle liquid providing a water repellent water vapour barrier. This allows internal moisture to be released without damage to the surface, whilst providing a water barrier to prevent further water ingress.

Reduction in surface dirt pick-up. Often caused by soluble soot's in rain. These dirty droplets will simply be shed off the wood surface with rain.

Reduction in splitting warping and checking. Wood changes its physical dimensions with the uptake of moisture. This also promotes the growth of micro-organisms and insect attack.

Reduction in mould, fungal and other microbial infestations. The treatment contains a long term film fungicide to assist in preventing fungal attack. Most fungal and algae growth take place on damp or wet substrates.

Caution

Once absorbed the substrate will show no outward sign of treatment. Some surfaces might darken slightly but no other change to the appearance or texture will be visible. 100% solubility in water; no turbidity or haze of the liquid phase in clear systems

Safety and Handling	Please read Material Safety Data Sheet (MSDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT[®] Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001 : 2015.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV
Speltdijk 1
NL-5704 RJ Helmond
The Netherlands
Tel: + 31 - 492 - 59 - 75 - 75
Fax: + 31 - 492 - 55 - 29 - 55
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

Publication Number HY83237
© ADDAPT Chemicals BV 2003
Version 4 : 2019

