

## ADDAPT<sup>®</sup> Foamstop<sup>™</sup> EM 19 Foam Control Agent

## Typical chemical and physical properties

ADDAPT® Foamstop™ EM 19 is a silicone-free highly effective foam control agent based on renewable resources; VOC and APEO free.

It is an emulsion of surface active components and edible oil in water.

ADDAPT® Foamstop™ EM 19 comply with the FDA regulation #173.340 (Incidental contact with foodstuff)

Appearance White, milky liquid

Active content 49 – 51%

Density at 25 °C 0.94 – 0.99 g/cm<sup>3</sup>

Viscosity at 25 °C <750 mPa·s

(Brookfield #3, 50 rpm)

Flash point >250 °C

Solubility

Water Emulsifiable

This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.

# Applications and typical treat level recommended

0.30 to 0.5 % wt. based on total formulation

#### **Benefits**

ADDAPT<sup>®</sup> Foamstop™ EM 19 is recommended for emulsion paints, high gloss emulsions paints, also for emulsions plasters.

 $\mathsf{ADDAPT}^{\otimes}$  Foamstop  $\mathsf{^{TM}}$  EM 19 may also be used in the production of emulsions binders.

ADDAPT® Foamstop $^{\text{TM}}$  EM 19 is easily emulsifiable. 2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage.

ADDAPT $^{\otimes}$  Foamstop  $^{\text{TM}}$  EM 19 maintains the defoaming and deaerating properties over a prolonged period of time.

ADDAPT<sup>®</sup> Foamstop™ EM 19 does not contain APEO derivatives, silicones, amines, nitrate/nitrite and fluorides.

ADDAPT<sup>®</sup> Foamstop<sup>™</sup> EM 19 is VOC free and MOSH/MOAH free.

No intercoat adhesion problems are expected when the defoamer is applied.





## ADDAPT® Foamstop™ EM 19

Product Specification

This information is available on request through our local representative.

Packaging

This information is available on request through our local representative.

The objective of our quality policy is the continuous fulfilment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN-EN-ISO-Standard 9001: 2015.

#### Liabilities

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 NL-5704 RJ Helmond The Netherlands Tel: +31 -492 -59 75 75

Fax: + 31 - 492 - 55 29 55 E-mail: info@addapt-chem.com

Home page: <a href="http://www.addapt-chem.com">http://www.addapt-chem.com</a>



Publication Number FO82625 © ADDAPT Chemicals BV 2022 Version 5: 2022