

Typical chemical and physical properties Acts as a solvent-free, readily biodegradable wetting agent for aqueous systems such as cleaning agents and (paper) coatings.

Polyhydroxy amide.

Appearance	Liquid
Solubility	
Water	Miscible
Odour	Barely perceptible
Density at 25°C	1,13 - 1,18 g/ml
pH at 23°C	5,0 - 8,0
Viscosity at 25°C	<50 mPa·s

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets	Coating industry Paper industry Ink industry Cleaning industry
Applications	Coatings and lacquers Paper coatings/impregnation Printing inks (OPV) Cleaner agents
Recommended dosage/usage	0,5 -2,0 % wt. based on total formulation

Key benefits

- Readily biodegradable -- Biobased -- APEO/NPEO free -- Solvent free -

- The multifunctional nature allows to provide the necessary wetting properties for water-based systems such as paints: adhesives; printing inks.
- Found to be an excellent carrier for water-soluble chemicals that must be placed on/in hydrophobic surfaces.
- Exhibits a high surface energy that leads to an excellent wetting of the (paper) coating without an increase of the water absorption (low COBB value).
- Non-foaming.
- Recommended to improve:
 - Wet-edge (open time) of emulsion paints and lacquers.
 - Gloss of emulsion lacquers.
 - The “flop” effect of aluminium pigments.
 - Anti-corrosion properties for ferrous substrates
 - Flow characteristics of both paper coatings and sizing.
- pH application range: 4 - 13.
- No hazard (H) and precaution (P) labelling necessary.

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)

Quality Policy The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

Liabilities *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV
Speltdijk 1
5704 RJ Helmond
The Netherlands
Tel: + 31 (0)492 597575
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

