

DEFEX[™] P25

Defoamers – Coatings & Industrial Article number: Verification date: Version:

FO82585 01/08/2024

Proprietary blend of organophosphates and glycol ethers.

Custom

Product description

Application and treat level

Defoamer/deaerator especially formulated for concrete and other industries such as the production of recycled paper/pulp.

Typical chemical and physical properties

Chemical nature Solubility

Water

Markets

Applications

Concrete industry

Paper industry

Concrete Paper

Dispersible

Apply the product in its natural state by aspersion or by dosing pump and adjust the initial dosage according to the requirements. May also be distributed with a water dilution system and or with a special metering system for automatic dosing to the process, which means product will automatically added only when needed.

100 – 250 ppm

Key benefits

- Free of MOSH/MOAH -- Free of silicone oils -

· Shows excellent performance in the control of foams and improves the flow.

- · Can be used to reduce the effects of too much air in concrete and bring the concrete back to its original strength.
- · Show excellent alkali stability.

Recommended dosage/usage

- · Leaves no residues in the pipes or valves of the equipment used.
- · Can be used in processing recycled paper in the chlorine dioxide process.
- · Can also be used as in detergents for dish washing machines.
- The foam-control agent is more accurately called de-aerating wetting agent.







DEFEX[™] P25

Defoamers – Coatings & Industrial FO82585 01/08/2024 Article number:

Verification date: Version:

Custom

Please read Safety Data Sheet (SDS) before handling. Safety and Handling Product Specification This information is available on request through our local representative. This information is available on request through our local representative. The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS) The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance. The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

Liabilities

Packaging

Quality Policy

Storage

All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.

ADDAPT Chemicals BV Speltdijk 1 5704 RJ Helmond The Netherlands Tel: + 31 (0)492 597575 E-mail: info@addapt-chem.com Home page: http://www.addapt-chem.com





