

**Typical chemical and physical properties** Cost-effective and sustainable foam control agent emulsion.

**Emulsion of surface-active components and vegetable oils in water.**

Appearance	White Liquid	
Active content	~50%	
Solubility		
Water	Emulsifiable	
Density at 25°C	0,94 - 0,99	g/ml
Viscosity at 25°C	300 - 750	mPa·s

*This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.*

**Application and treat level**

Markets	Coating industry Stearates industry Cleaning industry Water treatment industry
Applications	Paints Adhesives Floor polish Wastewater treatment
Recommended dosage/usage	0,30 to 0,5 % wt. based on total formulation  2/3 of the amount should be added during the grinding stage, 1/3 during the 'let down' stage

**Suitable as Incidental food contact**

**Key benefits**

- **Readily biodegradable -- Biobased -- VOC free -- APEO/NPEO free -- Free of MOSH/MOAH -- Free of silicone oils -- Free of amines -- Free of nitrates -- Free of nitrites -**
- Enhances gloss in certain emulsion-based paint systems due to improved levelling.
- Suitable for emulsion paints, high gloss emulsions paints, and also for emulsion-based plasters.
- May also be used in the production of emulsions binders.
- Easily emulsifiable.
- Maintains the defoaming and deaerating properties over a prolonged period of time.
- No intercoat adhesion problems are expected when the defoamer is applied.
- Cost-effective.
- Easy to incorporate.

---

<b>Safety and Handling</b>	Please read Safety Data Sheet (SDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.
<b>Storage</b>	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)

---

**Quality Policy** The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

---

**Liabilities** *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
5704 RJ Helmond  
The Netherlands  
Tel: + 31 (0)492 597575  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

