

Technical Data Sheet

WaxMul™ C 325

Wax Emulsion

Article number: Verification date: Version: W88922 18/02/2025 2.1

Typical chemical and physical properties T3-type carnauba wax dispersion in water. It is used in the paint industry, floor polish industry, car polish industry, shoe-and leather care and printing ink industry. Provides very good surface slip, scratchresistance, good water-repellent properties and increased gloss. It also improves the release and antiblock properties. Highly suitable for use in water-based (car) polishes and coatings.

Wax dispersion based on T3-type carnauba wax in water.

Appearance	Liquid	
Active content	~25%	
Solid content	24,0 - 26,0	wt%
Density at 25°C	0,98 - 1,02	g/ml
pH at 25°C	5,0 - 9,0	
Viscosity at 25°C	<50	mPa⋅s

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and		
treat level	Markets	Coating industry Ink industry Polish industry Leather industry
	Applications	Water-based coatings Floor polishes Car polishes Shoe- and leather care Printing inks
	Recommended dosage/usage	1,5% - 2,5%
Key benefits	- Inherently biodegradable Bio	

• Increases gloss and scratch resistance in polishes.

• Improves release and anti-block properties.

• Gives good water-repellent properties.







Technical Data Sheet

WaxMul™ C 325

Wax Emulsion

Article number: Verification date: Version: W88922 18/02/2025 2.1

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.	
Product Specification	This information is available on request through our local representative.	
Packaging	This information is available on request through our local representative.	
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)	
Quality Policy	The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance. The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.	
Liabilities	All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.	

ADDAPT Chemicals BV Speltdijk 1 5704 RJ Helmond The Netherlands Tel: + 31 (0)492 597575 E-mail: <u>info@addapt-chem.com</u> Home page: <u>http://www.addapt-chem.com</u>





