

### Typical chemical and physical properties

ADDAPT<sup>®</sup> Tac W 20 is a water soluble tack improver. It has an excellent thickening effect for water based systems.

Appearance	Viscous, clear liquid
Viscosity at 40 °C	1000 - 3000 cSt
Spec Gravity 25 °C	1.00-1.04 g/cm <sup>3</sup>
Flash point	n.a.

*This information is intended as a guideline only. For specifications please consult the Certificate of Analyses.*

### Applications and typical treat levels recommended

Metalworking processes, water based rust preventives.	0.5 to 5 % in the final, ready to use solution
---	--

Stir for min. 5 - 10 minutes.  
Warm water will emulsify the tackifier faster.

Stir until a nice smooth solution has been obtained.

### Benefits

The adhesion of fluids is significantly improved by Tac W 20 so that undesirable splashing of lubricants is considerably reduced.

# ADDAPT<sup>®</sup> Tac W 20

---

<b>Safety and Handling</b>	Please read Material Safety Data Sheet (MSDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.

---

**Quality Policy**                      The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT<sup>®</sup> Chemicals BV is based on the principles of the NEN-EN--ISO-Standard 9001: 2015.

---

**Liabilities**                              *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
NL-5704 RJ Helmond  
The Netherlands  
Tel: + 31 - 492 - 59 - 75 - 75  
Fax: + 31 - 492 - 55 - 29 - 55  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

Publication Number T87719  
© ADDAPT Chemicals BV 2003  
Version 4: 2019

