

Typical chemical and physical properties Corrosion inhibitor for high performance Engine Coolant, free of silicates, amines, phosphates, nitrites, nitrates and 2-Ethyl Hexanoic Acid.

Aqueous solution of organic acids salts.

Freezing point	-10°C	
Solubility		
Water	Soluble	
Density at 20°C	1,1 - 1,15	g/ml
Colour	≤500	Pt-Co
Foaming tendency test	Low	
Water content 8% in MEG	≤5	wt%

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets	Automotive industry Machinery
Applications	Engine coolants Antifreeze
Recommended dosage/usage	The requirement of ASTM D 3306 or ASTM D 4985 are generally met by adding 8% w/w of Coolant SEHF-8SC to MEG or MPG. Add Coolant SEHF-8SC to the MEG or MPG and homogenize for 30 minutes.

International, National and Military Standards met by Engine Coolant based on Coolant SEHF-8SC:
BS 6580 (UK) – FVV Heft R 443 (D) – Afnor R 15/601 (1) (F) – SAE J 1034 (1) – JIS K 2234 (1) (J) – KSM 2142 (K) – CUNA NC 956-16 (I) – UNE 26361-88 (E) – EMPA (CH) – ASTM D 3306 and 4985 – NATO S 759 – E/L 1415c (MIL Italy)

OEM Specifications met by Engine Coolant based on Coolant SEHF-8SC:
Porsche/VW/Audi/Seat/Skoda TL 774 D/F (2) – DTFR 29C110 – Ford ESE M97B49-A – CUMMINS 85T8-2 (1) – Man N. Man 248 and 324SNF – Wartsilia 32-9011 (C.W.) – Pegaso GM US 6277 M – Renault 41-01-001 – Ford WSS-M97B44-D – Chrysler MS 9176 – CUMMINS 90T8-4 – Mack 014GS17004 – MAN B&W D 36 5600 – GM 1899 M (1) – Navistar B-1, Type III – VOLVO (Reg. No 260) – FORD ESD M97 B49-A – OPEL GM QL 130100 – Leyland Trucks LTS 22 AF 10 – John Deere H 24 B1 and C1 – Deutz/MWN 0199-2091 2 Auflage (C.W.)

(1) Except reserve alkalinity – (C.W.) = coolant water (no MEG)

(2) Except water content

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)
Quality Policy	The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance. ☐ The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.
Liabilities	<i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i>

ADDAPT Chemicals BV
Speltdijk 1
5704 RJ Helmond
The Netherlands
Tel: + 31 (0)492 597575
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

