

Typical chemical and physical properties Water-soluble tackifier. It provides an excellent thickening and anti-splash effect for water-based systems.

Appearance	Clear liquid
Odour	Mild
Density at 25°C	1,05 - 1,15 g/ml
Viscosity at 25°C	1,00 - 4,00 Pa·s

This information is intended as a guideline only. For specifications please consult the Certificate of Analysis.

Application and treat level

Markets	Metalworking industry
Applications	Metalworking processes Water-based rust preventives
Recommended dosage/usage	0,5 to 5,0% in the final, ready to use solution. After adding, stir for 5 - 10 minutes. Warm water will emulsify the tackifier faster. Stir until a nice smooth solution has been obtained.

Suitable as Food contact material

Key benefits

- Readily biodegradable -- PFAS Free -- Free of MOSH/MOAH -- Free of silicone oils -
- The adhesion of fluids is significantly improved so that undesirable splashing of lubricants is considerably reduced.
- Improved (water-based) lubricant adhesion and efficiency.
- Reduces splashing.
- Non-flammable.

Safety and Handling	Please read Safety Data Sheet (SDS) before handling.
Product Specification	This information is available on request through our local representative.
Packaging	This information is available on request through our local representative.
Storage	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)
Quality Policy	The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance. ☐ The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.
Liabilities	<i>All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.</i>

ADDAPT Chemicals BV
Speltdijk 1
5704 RJ Helmond
The Netherlands
Tel: + 31 (0)492 597575
E-mail: info@addapt-chem.com
Home page: <http://www.addapt-chem.com>

