

**Typical chemical and physical properties** Corrosion inhibitor package for high-performance engine coolant, 100% silanized organic acid technology, 2-Ethyl Hexanoic Acid free.

**Concentrated aqueous solution of organic acids salts (Si-OAT technology).**

Freezing point	-18°C
Solubility	
Water	Soluble

**Application and treat level**

Markets	Automotive industry Machinery
Applications	Engine coolants Antifreeze
Recommended dosage/usage	The requirement of ASTM D 3306 or ASTM D 4985 are fully met by adding 10% w/w of Coolant SEHF-12SC to MEG or MPG.  Add Coolant SEHF-12SC to the MEG and homogenize for 30 minutes.

**Key benefits**

International, National and Military Standards met by Engine Coolant based on Coolant SiF-12SC:  
BS 6580 (GB) – FVV Heft R 443 (D) – Afnor R 15/601 (1) (F) – SAE J 1034 (1) – JIS K 2234 (J) – KSM 2142 (K) – CUNA NC 956-16 (I) – UNE 26361-88 (E) – EMPA (CH) – ASTM D 3306 and 4985 – NATO S 759 – E/L 1415c (MIL Italy)

OEM Specifications met by Engine Coolant based on Coolant SEHF-12SC:

Audi/Bentley/Bugatti/Lamborghini/Seat/Skoda/VW TL 774 G – Cummins CES 14603 – Deutz DQC cc-14 – Deutz-Fahr >04/2017 – Ducati Irizar >09/2016 – Liebherr Minimum LH-01-COL3A – MAN Diesel & Turbo BASF-CW-GLY00G40-01 – Man Truck & Bus Man 324 Typ 324 Typ Si-OAT – Mercedes-Benz Cars MB-325.5 & MB-325.6 & MB-326.6 – Mercedes-Benz Truck & Bus MB-325.5 & MB-326.6 – MTU MTL 5048 – Porsche >2010 – SETRA MB 325.5 – Smart MB 325.6 – in proper basestock VW TL 774-J

<b>Safety and Handling</b>	Please read Safety Data Sheet (SDS) before handling.
<b>Product Specification</b>	This information is available on request through our local representative.
<b>Packaging</b>	This information is available on request through our local representative.
<b>Storage</b>	The product should be stored at a temperature of no less than 10 °C and no more than 25 °C and away from light. For more safety details read the Safety Data Sheet (SDS)

**Quality Policy** The objective of our quality policy is the continuous fulfillment of the internal and external requirements agreed upon with our partners with regards to everybody's performance.

The Quality System of ADDAPT® Chemicals BV is based on the principles of the NEN - EN - ISO - Standard 9001:2015.

**Liabilities** *All recommendations for the use of our products, whether given by us in writing, orally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations, buyer or user remains responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility thereof. Buyer has to ensure that the intended use of the products will not infringe any third party's intellectual property rights. We warrant that our products are free from defects in accordance with, and subject to, our general conditions of sale and supply.*

ADDAPT Chemicals BV  
Speltdijk 1  
5704 RJ Helmond  
The Netherlands  
Tel: + 31 (0)492 597575  
E-mail: [info@addapt-chem.com](mailto:info@addapt-chem.com)  
Home page: <http://www.addapt-chem.com>

